

Product Data Sheet

MAK RUSTROL 271

DESCRIPTION

It is low viscosity, de-watering rust protective with ability to displace water from metallic surfaces, spreading rapidly to form a rust preventing film at the same time. It is solvent based product, where the solvent evaporates on application of the product to the metal surface, leaving the rust preventive on the place.

PERFORMANCE BENEFITS

- It contains additives, which suppresses the corrosive attack that may be caused by fingerprints through the presence of salts due to perspiration
- In conjunction with packaging or wrapping, this is suitable for long term protection.

APPLICATION

The product is required for protection of metal parts and assemblies during the manufacture process and when stored indoors. The product is particularly suitable for the applications where protected components are regularly handled but quick removal of the film is not required.

PERFORMANCE LEVEL

Characteristics	IS 1448	Typical Figures
Appearance	--	Brown liquid
Specific gravity @ 29.5°C		0.810
K.V at 40° C, cSt	P:25	1.771
Flash Point, (Abel), °C	P:69	39.0
Film type	--	Dry & soft
Film coverage, sq.mtr / ltr	IS: 1154:2000 appendix A	260
Film thickness, microns	IS: 1154:2000 appendix A	3.8
Stability in cyclic temp.	IS: 1674:1960 appendix C	Stable

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A¹ Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 110 / Issue 1 / Oct, 2008