

Product Data Sheet

MAK BRAKE FLUID XT

DESCRIPTION

It is premium quality fully synthetic hydraulic brake fluid specially designed to withstand severe heat and moisture conditions.

It is recommended for modern vehicles fitted with disc brakes as they operate under severe conditions leading to generation of higher temperatures especially in city stop-and-go conditions requiring frequent braking.

APPLICATIONS

This oil is recommended for use in both disc and drum brake systems of modern vehicles.

PERFORMANCE BENEFITS

- Has a very high reflux boiling point
- Good fluidity and stability even at low temperatures to make braking effective

PERFORMANCE LEVEL

- FMVSS-116 DOT-4
- IS 8654 : 2001
- SAE-J-1703

Characteristics	Requirement	Typical Figures
Appearance	Clear & Bright	Clear & Bright
Equilibrium Reflux Boiling point, (ERBP) °C, min.	230	240
Wet ERBP, °C, min.	155	160
KV, cSt		
at -40°C, max.	1800	1600
at 100°C, min.	1.5	2.2
pH	7.0 to 11.5	9.7

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Auto / 037 / Issue 1 / Oct, 2008