

Product Data Sheet

MAK CABOL

ISO VG: 15, 22, 32, 46, 68, 100, 150, 220, 320 & 460

Non ISO VG: 121, 176 & 257

DESCRIPTION

These are highly refined high viscosity index mineral oils which maintain a thin film of oil under light & medium load conditions.

PERFORMANCE BENEFITS

- Exhibit good oxidation & thermal stability
- Provide protection against corrosion & rust even during idle condition

APPLICATIONS

These are used in bearing applications in various industries such as steel, textile, pharmaceutical, chemical, processing industries etc.

PERFORMANCE LEVEL

- IS 493 (Part 1) : 1981 [Reaffirmed Nov., 1998]

Our grades meet above specification for the respective viscosity grades.

Characteristics	IS 1448	Typical Figures			
		15	22	32	46
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Density at 15° C	P:16	0.8651	0.8664	0.8819	0.8827
K.V at 40° C, cSt	P:25	15.1	22.9	32.3	46.2
Viscosity Index	P:56	102	101	100	100
Pour Point, °C	P:10	-9	-9	-9	-9
Flash Point, (COC), °C	P:69	168	188	210	220
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a	1a	1a	1a

Characteristics	IS 1448	Typical Figures		
		68	100	121
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright
Density at 15° C	P:16	0.8835	0.8876	0.8902
K.V at 40° C, cSt	P:25	68.4	100.7	121.8
Viscosity Index	P:56	98	96	95
Pour Point, °C	P:10	-6	-6	-6
Flash Point, (COC), °C	P:69	220	232	240
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a	1a	1a

Product Data Sheet



Characteristics	IS 1448	Typical Figures		
		150	176	220
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright
Density at 15° C	P:16	0.8930	0.8942	0.8966
K.V at 40° C, cSt	P:25	150.2	175.9	220.5
Viscosity Index	P:56	95	94	94
Pour Point, °C	P:10	-6	-6	-6
Flash Point, (COC), °C	P:69	244	246	250
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a	1a	1a

Characteristics	IS 1448	Typical Figures		
		257	320	460
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright
Density at 15° C	P:16	0.8966	0.8986	0.8998
K.V at 40° C, cSt	P:25	257.1	320.7	460.5
Viscosity Index	P:56	93	93	92
Pour Point, °C	P:10	-6	-6	-6
Flash Point, (COC), °C	P:69	252	256	280
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a	1a	1a

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 001 / Issue 1 / Oct, 2008

MAK[®] makes it possible