

Product Data Sheet

MAK SHOCK ABSORBER FLUID-1F

DESCRIPTION

This is specially formulated fluid for use in latest design automotive shock absorbers.

PERFORMANCE BENEFITS

- Ensures smoother ride by excellent dampening of shock loads
- Provides very high degree of chemical stability
- Good seal compatibility
- very low pour point which will enable its use over wide temperature range

APPLICATIONS

These are approved by M/s Munjal Showa Ltd.

PERFORMANCE LEVEL

- Proprietary brand

Characteristics	IS 1448	Typical Figures
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Red
Density @15°C	P:16	0.9010
K.V at 40° C, cSt	P:25	35.5
Viscosity Index	P:56	106
Flash Point, (COC), °C	P:69	186
Pour Point, °C	P:10	<-42
Aniline point, °C	P:3	82.7
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	10 / Nil
b) Sequence II		10 / Nil
c) Sequence III		10 / Nil

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Auto / 040 / Issue 1 / Oct, 2008