# MAK® LUBRICANTS

### **Product Data Sheet**

## **MAK SHOCK ABSORBER FLUID-2R**

#### **DESCRIPTION**

This is specially formulated fluid for use in latest design automotive shock absorbers.

#### **APPLICATIONS**

These are approved by M/s Munjal Showa Ltd.

#### **PERFORMANCE BENEFITS**

- Ensures smoother ride by excellent dampening of shock loads
- Provides very high degree of chemical stability
- Good seal compatibility
- very low pour point which will enable its use over wide temperature range

#### PERFORMANCE LEVEL

· Proprietary brand

Characteristics	IS 1448	Typical Figures
Appearance		Clear & Bright
Colour, Visual Observation		Brown
Density @15°C	P:16	0.8784
K.V at 40° C, cSt	P:25	17.2
Viscosity Index	P:56	110
Flash Point, (COC), °C	P:69	174
Pour Point, °C	P:10	-24
Aniline point, °C	P:3	83
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	10 / Nil
b) Sequence II		10 / Nil
c) Sequence III		10 / Nil

#### **Health and Safety**

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.** 

**Technical Services** 

A' Installation, Sewree (East), Mumbai – 400 015 Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

Edition: R&D / Auto / 041 / Issue 1 / Oct, 2008