

## Product Data Sheet

# MAK SHOCK ABSORBER FLUID-DS

### DESCRIPTION

This is a tailor made oil blended with superior base oils and fortified with anti-wear, anti-rust and anti-foam additives.

### PERFORMANCE BENEFITS

- Very good seal compatibility
- Excellent dampening characteristics
- Good anti-foam, anti-wear and anti-rust properties
- Very low pour point which enables its usage over a wider temperature range

### APPLICATIONS

It is approved by M/s Duroshox for Shock Absorbers manufactured by them

### PERFORMANCE LEVEL

- Proprietary brand

Characteristics	IS 1448	Typical Figures
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Brown
Density @15°C	P:16	0.8767
K.V at 40° C, cSt	P:25	12.7
Viscosity Index	P:56	76
Flash Point, (COC), °C	P:69	180
Pour Point, °C	P:10	-39
Aniline point, °C	P:3	82
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	10 / Nil
b) Sequence II		10 / Nil
c) Sequence III		10 / Nil

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

Edition: R&D / Auto / 044 / Issue 1 / Oct, 2008